

## ALIGNER AND DEVICE FABRICATION METHOD

### BACKGROUND OF THE INVENTION

#### Field of the Invention

5           The present invention relates to an aligner used to fabricate a semiconductor device, liquid-crystal display device or thin-film magnetic head.

#### Related Background Art

          It is requested for an aligner such as a  
10 semiconductor aligner to expose a photoconductor such as a wafer at a target light exposure. It is difficult to control a light exposure on the photoconductor by directly measuring the light exposure. Therefore, a conventional aligner takes  
15 out some of illumination light emitted from a light source by a half mirror and measures it by a quantity-of-light detector to control a light exposure so that a photoconductor is exposed at a target light exposure in accordance with the measured  
20 value of the quantity-of-light detector. A relation between a value of the quantity-of-light detector and an actual quantity of light of the photoconductor is previously calibrated.

          A recent aligner has to use an ArF excimer  
25 laser beam having a shorter wavelength as a light source in accordance with a request for miniaturizing a semiconductor. However, because some of the ArF

excimer laser beam is absorbed in oxygen molecules and consumed as the energy for ozonization, a light exposure is decreased. Therefore, it is necessary to consider an oxygen density on an optical path.

5 Moreover, because the oxygen density on the optical path is fluctuated (decreased) due to ozonization, an exposure energy quantity to be absorbed in oxygen molecules is not constant. To solve this problem, a method is already proposed which realizes high-  
10 accuracy light exposure control by using means for measuring an oxygen density on the optical path of illumination light and correcting a light exposure in accordance with the measured value (Japanese Patent Application Laid-Open No. H11-87230).

15 However, because of a request for further miniaturizing an aligner, it is demanded to use the  $F_2$  excimer laser beam having a wavelength shorter than that of an ArF excimer laser beam. When using the  $F_2$  excimer laser beam as a light source, some of  
20 the excimer laser beam is absorbed in not only oxygen but also moisture on an optical path. Therefore, when using the  $F_2$  excimer laser beam as a light source, it is necessary to control not only an oxygen density but also a moisture density. Therefore, a  
25 light exposure is not proper unless a moisture density is proper even if an oxygen density is proper.

It is an illustrative object of the present

invention to solve problems of the prior art and  
provide an aligner capable of performing a proper  
light exposure control in accordance with an oxygen  
density and moisture density on an laser beam optical  
5 path.

#### SUMMARY OF THE INVENTION

According to the present invention, there is  
provided an aligner for illuminating a mask (or  
10 reticle) with light emitted from a light source and  
exposing an object to be exposed with light reflected  
from the mask, comprising:

oxygen density detection means for detecting an  
oxygen density on an optical path between the light  
15 source and the object to be exposed;

moisture density detection means for detecting  
a moisture density on the optical path; and

control means for controlling a light exposure  
to be irradiated to the object to be exposed based on  
20 the detection results of the oxygen density detection  
means and the moisture density detection means.

In the aligner according to present invention,  
quantity-of-light detection means is included which  
detects a quantity of light at a predetermined  
25 position on the optical path.

In the aligner according to present invention,  
light exposure detection means is included which

detects a quantity of light irradiated to the object to be exposed.

In the aligner according to present invention, the control means controls the light exposure in  
5 accordance with a relation between an absorbed quantity of light emitted from the light source (absorptance of light having a wavelength emitted from the light source) and an oxygen density (relation between absorbed quantity of light  
10 irradiated to the object to be exposed and a certain oxygen density).

In the aligner according to present invention, a relation between an oxygen density and an absorptance of light emitted from the light source is  
15 previously included as data.

In the aligner according to present invention, the control means controls the light exposure in accordance with a relation between an absorbed quantity of light emitted from the light source  
20 (absorptance of light having a wavelength emitted from the light source) and a moisture density (relation between an absorbed quantity of light irradiated to the object to be exposed and a certain moisture density).

25 In the aligner according to present invention, a relation between a moisture density and an absorbed quantity of light emitted from the light source is

previously included as data.

In the aligner according to present invention, the light emitted from the light source is an excimer laser beam.

5 In the aligner according to present invention, the excimer laser beam is an F<sub>2</sub> laser beam.

In the aligner according to present invention, the control means has an ND filter and the ND filter controls a light exposure to be irradiated to the  
10 object to be exposed.

In the aligner according to present invention, the control means has a diaphragm to control a light exposure to be irradiated to the object to be exposed by changing opening diameters of the diaphragm.

15 According to the present invention, there is provided a device fabrication method comprising:

a step of exposing the object to be exposed by using the aligner of present invention; and

a step of developing the exposed object.

20 According to the present invention, there is provided an aligner for transferring a pattern formed on a mask or reticle to an object to be exposed comprising:

quantity-of-light detection means for detecting  
25 a quantity of exposure light;

oxygen density detection means for detecting an oxygen density in an exposure environment;

moisture density detection means for detecting  
a moisture density in the exposure environment; and

control means for controlling the quantity of  
the exposure light in accordance with data showing  
5 the relation between the oxygen density, the moisture  
density and the absorbed quantity of the exposure  
light and detection results by the oxygen density  
detection means and the moisture detection means  
previously obtained.

10 According to the present invention, there is  
provided a device fabrication method comprising:

a step exposing the object to be exposed by  
using the aligner of present invention; and

a step of developing the exposed object.

15 Increasing objects and other characteristics of  
the present invention will become more apparent by  
preferred embodiments to be described by referring to  
the following drawings.

## 20 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic block diagram of an  
essential portion of an aligner of an embodiment of  
the present invention;

FIG. 2 is a flowchart for calculating a  
25 correction value used for light exposure control of  
the present invention;

FIG. 3 is a schematic block diagram of the

aligner further comprising quantity-of-light change means shown in FIG. 1;

FIG. 4 is a flowchart for explaining the light-exposure control operation by the quantity-of-light change means shown in FIG. 3;

FIG. 5 is a flowchart for explaining a method for fabricating a device having an aligner of the present invention; and

FIG. 6 is a detailed flowchart of the step 4 shown in FIG. 5.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

An aligner of an embodiment of the present invention is described below by referring to FIG. 1.

15 In this case, FIG. 1 is a schematic block diagram of an essential portion of an aligner relating to this embodiment. In FIG. 1, reference numeral 1 denotes an  $F_2$  excimer laser beam source. Reference numeral 2 denotes a chamber A holding a not-illustrated

20 illumination optical system in which the chamber A is hermetically closed so that ambient air does enter the chamber A and nitrogen is injected from the outside. The chamber A includes an optical system (such as mirror for folding optical path) for leading

25 an excimer laser beam emitted from the excimer laser beam source 1 to a chamber B to be described later and an optical integrator.

Reference numeral 3 denotes a half mirror which divides a quantity of light transmitted through an illumination optical system. Reference numeral 4 denotes a light exposure detector A for detecting quantities of light divided the half mirror 3, which indirectly measures a light exposure difficult to directly measure during exposure on the surface of a not-illustrated wafer. Reference numeral 5 denotes a chamber B in which the remaining components of the lighting optics and a light-projection optical system for projecting an integrated circuit pattern formed on a not-illustrated mask or reticle is set. The chamber B is also hermetically closed so that ambient air does not enter the chamber B similarly to the case of the chamber A and nitrogen is injected from the outside so that an oxygen density and moisture density can be decreased.

In the case of this embodiment, the chamber A is separated from the chamber B. However, it is also allowed to constitute the both chambers A and B as an integrated chamber. Moreover, it is allowed to separately constitute an illuminating chamber for receiving light from a light source and leading it up to a wafer and a projecting chamber for receiving light from a reticle and leading it up to a wafer. Furthermore, it is allowed to constitute the illuminating chamber by a plurality of chambers, the



projecting chamber by a plurality of chambers or the both chambers by a plurality of chambers.

Reference numeral 6 denotes an oxygen-moisture densitometer for detecting an oxygen density and moisture density in a chamber B5. It is recommended to set detection sections of the oxygen-moisture densitometer 6 on an optical path because it is preferable to directly detect an oxygen density and moisture density on the optical path. However, when the optical path is interrupted by a detection section on the optical path, it is also allowed to set the detection section nearby the optical path. Moreover, a measuring position is not restricted when it is possible to calculate an oxygen density and moisture density on the optical path in accordance with measured values of the oxygen moisture densities by previously measuring the oxygen and moisture densities on the optical path and at a position which is not nearby the optical path and examining the relation between measured values at the position and measured values of the oxygen and moisture densities on the optical path (through a simulation or the like). It is more preferable to use a plurality of measuring positions than one measuring position and it is preferable to measure oxygen and moisture densities at each position and calculate the transmittance of light at each position and then

control a light exposure in accordance with the  
calculated result. It is also allowed to average  
measured results at a plurality of positions.

It is principally allowed to set the oxygen-  
5 moisture densitometer 6 at any position. When oxygen  
and moisture densities at a certain position can be  
obtained, it is possible to calculate a transmittance  
by the following expression in accordance with an  
absorptance by oxygen and moisture and an optical  
10 path length (excluding a lens thickness) up to the  
position.

(Numerical formula 1)

Transmittance =  $\text{EXP}^{-(\text{absorptance}) \times (\text{density})}$   
15  $\times (\text{optical path excluding lens thickness})$

Therefore, because the transmittance is  
calculated at the position when a plurality of  
measuring positions is used, it is possible to more  
20 accurately obtain a relation between measured value  
and calculated value.

Reference numeral 7 denotes a light exposure  
detector B for detecting a light exposure immediately  
after passing through a not-illustrated projecting  
25 optical system, which is set on the surface of a not-  
illustrated wafer. The light exposure detector B7 is  
not used at the time of exposure but a light exposure

detector A4 is used.

Reference numeral 8 denotes a controller for storing and computing results obtained from the light exposure detectors A and B and the oxygen-moisture densitometer 6 and controlling the light emitted from the F<sub>2</sub> excimer laser beam source 1. The controller 8 includes a not-illustrated control section and a memory connected to the control section. The memory stores data showing a relation between oxygen density, moisture density and absorbed quantity of exposure light and a flowchart of the light exposure control operation of this embodiment to be described later by referring to FIGS. 2 and 4 as programs. The memory has a concept of including a volatile memory and a nonvolatile memory.

It is allowed to show data by a graph in which oxygen density or moisture density is assigned to the axis of abscissa and absorbed quantity of exposure light (%) is assigned to the axis of ordinate. Moreover, it is allowed to three-dimensionally show oxygen density, moisture density and quantity of exposure light absorbed in oxygen and moisture by a graph in which the oxygen density is assigned to X axis, moisture density is assigned to Y axis and quantity of exposure light absorbed in oxygen and moisture is assigned to Z axis. Furthermore, it is allowed to store a database showing a relation

between oxygen density, moisture density and absorbed quantity of exposure light in the memory instead of a graph.

In the case of this embodiment, the relation  
5 between the light exposure detectors A and B is obtained from values of the oxygen density and moisture density in the chamber B5.

First, it is possible to calculate the quantity of a laser beam absorbed in an optical system in the  
10 chamber B in accordance with the configuration of the optical system. The optical system includes not only a lens but also a mirror. In the case of the lens, the transmittance of the lens is shown by the following expression.

15

(Numerical formula 2)

Transmittance = glass transmittance (1/cm) ^  
glass thickness (cm)

20 Therefore, the quantity of light when passing through a lens is shown by the following expression.

(Numerical formula 3)

Quantity of light after transmission = Quantity  
25 of light before transmission x Transmittance

In the case of a mirror, the following

expression is applied.

(Numerical formula 4)

Quantity of light after reflection =

5 Reflectance of mirror  $\times$  Quantity of light before  
reflection

It is possible to similarly calculate the  
quantity of a laser beam absorbed in oxygen and  
10 moisture. It is possible to use the above three-  
dimensional graph for an absorbed quantity. For  
example, by using the graph, it is possible to  
calculate an absorptance of exposure light by oxygen  
molecules when an oxygen density is 3 ppm is 4.46%/m.  
15 Therefore, it is possible to calculate the light  
exposure on the surface of a not-illustrated wafer in  
accordance with the following expression.

(Numerical formula 5)

20  $E_B = E_A - C_B - O_B - W_B$

In the above expression,  $E_B$  denotes a value  
measured by the light exposure detector B7,  $E_A$   
denotes a value measured by the light exposure  
25 detector A4,  $C_B$  denotes a quantity of (transmission  
member and reflection member of) a laser beam  
absorbed in an optical system in the chamber B5,  $O_B$

denotes a quantity of a laser beam absorbed in oxygen molecules in the chamber B5 and  $W_B$  denotes a quantity of a laser beam absorbed in moisture in the chamber B5.

5           In fact, however, transmittance cannot be obtained from Numerical formula 1 but it can be obtained from the following Numerical formula 6.

(Numerical formula 6)

10           
$$E_B = E_A - C_B - O_B - W_B - F_B$$

          In the above expression,  $F_B$  denotes a correction value. The correction value  $F_B$  results from an unexpected error in an optical system, which is a  
15   correction value for correcting Numerical formula 1 and must be obtained before exposure. A method for calculating the correction value  $F_B$  is described below by referring to FIG. 2. In this case, FIG. 2 is a flowchart for explaining the method for  
20   calculating the correction value  $F_B$ .

          First, in step 21, nitrogen is injected into a chamber A2 to sufficiently saturate the chamber A2 with nitrogen, that is, to sufficiently replace air and nitrogen in the chamber A2. In other words,  
25   moisture and oxygen are removed. The expression "saturation" denotes an oxygen density and moisture density respectively stabilized at a certain value

after a long-enough time passes and gas replacement is performed. Then, in step 22, nitrogen is injected into the chamber B5 to operate the oxygen-moisture densitometer 6. Then, in step 23, a laser beam is  
5 emitted from the F<sub>2</sub> excimer laser beam source 1 by a predetermined number of pulses (e.g. three pulses). The number of pulses P<sub>M</sub> necessary for exposure can be obtained by the following expression in accordance with a light exposure E<sub>M</sub> necessary for exposure of a  
10 wafer and exposure energy E<sub>P</sub> per pulse. In this case, however, a sampling frequency necessary to obtain the correction value FB is set.

(Numerical formula 7)

15 
$$P_M = E_M / E_P$$

Then, in step 24, values of the light exposure detector A4, light exposure detector B7 and oxygen-moisture densitometer 6 are measured and stored in a  
20 (not-illustrated memory) of the controller 8.

Then, in step 25, it is determined whether the value of the oxygen-moisture densitometer is saturated. The value is determined to be saturated because it is necessary to store the difference  
25 (correction value in this case) between an expected simulation and an actual value in a controller and thereby, it is necessary to store data while gas is

sufficiently replaced as described above. In this case, when it is determined in step 25 that each value is not saturated, steps 23 and 24 are restarted to store values of light exposure, oxygen density and  
5 moisture density in the controller 8.

When each value is saturated, a laser beam is emitted in step 26 and stopped after step 24 is executed. Strictly, steps 23 and 26 respectively include a step of determining whether the number of  
10 pulses reaches a predetermined value and continuously emitting a laser beam until it is determined that the number of pulses reaches the predetermined value.

In step 27, the correction value  $F_B$  is calculated by Numerical formula 6. The calculated  
15 correction value  $F_B$  is stored in the controller 8 at any time. As described above, correction values are obtained in advance in accordance with various oxygen densities and moisture densities from a calculated oxygen density and moisture density.

20 Then, the excimer laser beam source 1 is corrected as described below at the time of exposure. First, the oxygen density and moisture density in the chamber B5 are measured by the oxygen-moisture densitometer 6. Then, based on the value, a quantity  
25 absorbed in oxygen and moisture in the chamber B5 is calculated by using Numerical formulas 1 to 4. At the same time, the correction value  $F_B$  at the oxygen



density and moisture density is read out from the controller 8. Moreover, the light exposure  $E_M (=E_B)$  necessary at the time of exposure is set to the light exposure detector B7 on the controller 8 in accordance with Numerical formula 6 to calculate a value  $E_A (= E_M+C_B+O_B+W_B+F_B)$  to be detected by the light exposure detector A4 in accordance with Numerical formula 6. A beam is emitted from the excimer laser beam source 1 until the necessary value  $E_A$  is reached while monitoring the light exposure detector A4 in accordance with the obtained value. When emitting one pulse of the laser beam, a part of the beam is absorbed in oxygen. However, because the number of oxygen molecules is decreased due to ozonization,  $O_B$  is decreased for the next pulse and thereby,  $E_A$  is changed whenever emitting the laser beam. Then, even if obtaining  $E_A$  after emitting several pulses, it may not be a necessary value any longer. In this case, by detecting an oxygen density and moisture density again and reading out the data based on the oxygen density and moisture density from the controller,  $E_A$  is calculated to correct the emission quantity of the laser.

A light exposure more than a necessary light exposure may be obtained. This is described below by referring to FIGS. 3 and 4. FIG. 3 is a schematic block diagram showing that quantity-of-light change

means is set to an aligner of the present invention.  
In FIG. 3, reference numeral 9 denotes an ND filter  
having a function for reducing the quantity of light  
of the  $F_2$  excimer laser source 1. FIG. 4 is a  
5 flowchart for explaining the quantity-of-light  
control operation using the ND filter 9.

In step 41, the ND filter 9 is set so that the  
maximum quantity of light passes through the filter.  
In step 42, it is communicated to the  $F_2$  excimer  
10 laser source to emit one pulse of a laser beam from  
the controller 8. In step 43, one pulse of an  $F_2$   
laser beam is emitted. In step 44, a light exposure  
is monitored by the light exposure detector A4 and as  
a result,  $E_A$  is transferred to the controller 8. In  
15 step 45, the light exposure obtained by a value  $E_{A1}$   
detected from "(set necessary light exposure  $E_M$  -  
accumulated light exposure  $E_{AP}$  obtained by the light  
exposure detector A4)/value  $E_A$  detected by light  
exposure detector A4" is computed by the controller 8  
20 to compute whether the obtained result is smaller  
than 1. In this case, when the result is not kept in  
the range, "already set light exposure  $E_M$  = already  
set light exposure  $E_M$  - accumulated light exposure  $E_{AP}$   
obtained by the light exposure detector A4" is set  
25 again to repeat steps 42 to 45. In step 46, when the  
obtained result is smaller than 1, a light exposure  
more than a necessary light exposure is obtained by

emitting one pulse of the final laser beam.  
Therefore, a quantity of light to be reduced by the  
ND filter 9 is computed by the controller 8 in  
accordance with the value obtained in step 45 to  
5 operate the ND filter 9. In step 47, only one pulse  
of the F<sub>2</sub> laser beam is emitted to complete the  
processing.

As described above, according to this  
embodiment, it is possible to perform a high-accuracy  
10 light exposure control during exposure even if the  
oxygen density and moisture density in the chamber B  
are any values. Moreover, even in the case in which  
a light exposure more than a necessary light exposure  
is obtained by emitting one pulse of the final laser  
15 beam, it is possible to obtain a proper light  
exposure by operating the quantity-of-light change  
means.

This embodiment uses an ND filter as a method  
for controlling a light exposure (quantity of light  
20 of exposure light reaching wafer). However, without  
being restricted to the above mentioned, it is also  
allowed to change opening diameters of an iris  
diaphragm or make the quantity of light emitted from  
a light source variable.

25 Then, an embodiment of a device fabrication  
method using the aligner shown in FIG. 1 or 3 is  
described below with reference to FIGS. 5 and 6. FIG.

5 is a flowchart for explaining fabrication of a device (semiconductor chip such as IC or LSI, or LCD or CCD). In this case, fabrication of a semiconductor chip is described as an example. In step 1 (circuit design), a circuit of a device is designed. In step 2 (mask making), a mask on which a designed circuit pattern is formed is made. In step 3 (wafer fabrication), a wafer is fabricated by using a material such as silicon. Step 4 (wafer process) is referred to as an upstream process in which an actual circuit is formed on a wafer through the lithography by using a mask and the wafer. Step 5 (packaging) is referred to as a downstream process which is a process for forming a semiconductor chip by using the wafer formed in step 4 and includes an assembly process (dicing and bonding) and a packaging process (chip sealing). In step 6 (testing), an operation confirmation test and a durability test of a semiconductor device fabricated in step 5 are performed. The semiconductor device is completed after passing through these processes and shipped (step 7).

FIG. 6 is a detailed flowchart of the wafer process in step 4. In step 11 (oxidation), the surface of the wafer is oxidized. In step 12 (CVD), an insulative film is formed on the surface of the wafer. In step 13 (electrode formation), an

electrode is formed on the wafer through vapor deposition or the like. In step 14 (ion implantation), ions are implanted into the wafer. In step 15 (resist processing), a photosensitive material is applied to the wafer. In step 16 (exposure), the circuit pattern of the mask is exposed to the wafer by the aligner shown in FIG. 1 or 3. In step 17 (developing), the exposed wafer is developed. In step 18 (etching), portions other than the developed resist image are shaved off. In step 19 (resist stripping), resist which is unnecessary because etching is finished is removed. By repeating these steps, circuit patterns are multiply formed on the wafer. According to the above device fabrication method, it is possible to fabricate a device having a higher quality than ever. Thus, a device fabrication method using an aligner and a device which is a resultant product constitute one side of the present invention.

20           The above device fabrication method effectively influences a device which is an intermediate and final resultant product. Moreover, the device includes a semiconductor chip such as an LSI or VLSI, CCD, LCD, magnetic sensor and thin-film magnetic head.

25           According to this embodiment, it is possible to provide an aligner capable of controlling a proper light exposure in accordance with an oxygen density and moisture density in an optical path.